

REFLECTED CEILING PLAN

SYMBOLS LEGEND: 1/8"=1'-0"

 2'-0"x2'-0" RECESSED FLOOR LIGHT FIXTURE
"E"EXIST'G TO REMAIN "R"REMOVE "N"NEW
LOCATION FOR EXIST'G

 2'-0"x4'-0" RECESSED FLUOR. LIGHT FIXTURE
"E"EXIST'G TO REMAIN "R"REMOVE "N"NEW
LOCATION FOR EXIST'G

 6" DIA. INCAND. DOWNLIGHT
NEW LOCATION FOR EXIST'G

 2'-0"x2'-0" HVAC SUPPLY OR RETURN GRILLE
SEE MECH. ENGR DWG. FOR SPECS.
"E"EXIST'G TO REMAIN "R"REMOVE "N"NEW

 EXIST'G CL'G MT'D ILLUMINATED EXIT SIGN

 BLD'G STD CL'G MT'D SPRINKLER HEAD
"E"EXIST'G TO REMAIN "R"REMOVE "N"NEW

 NEW BLDG STD WALL MT'D LIGHT SWITCH @44" A.F.F.
"E" EXIST'G TO REMAIN

NOTES:

1. ALL HARD LID CEILINGS, AND SOFFITS CANNOT CONNECT TO THE STOREFRONT BELOW THE STOREFRONT FRAMING SYSTEM.
2. EXIT SIGNAGE AT THE STOREFRONT MUST BE A RECESSED MOUNT ACRYLIC BLADE

ABOVE AND BEYOND
LASER SKIN CLINICS

15358 ALTON PARKWAY
IRVINE, CALIFORNIA

